

Safety signals

Important information concerning safety is distinguished in this manual by the following notations:



The Safety alert symbol means:

Caution! Your safety is involved.



Failure to follow warning instructions could result in severe or fatal injury

using the suspension, or to bystanders.



Caution indicates that special precautions must be taken to avoid damage to the suspension.



This indicates information that is of importance with regard to procedures.

Before installation

Ohlins Racing AB can not be held responsible for any damage whatsoever to steering damper or vehicle, or injury to persons, if the instructions for fitting and maintenance are not followed exactly. Similarly, the warranty will become null and void if the instructions are not adhered to.



1. Installing a steering damper, that is not approved by the vehicle manufacturer, may affect the stability of your vehicle. Ohlins Racing AB cannot be held responsible for any personal injury or damage whatsoever that may occur after fitting the steering damper. Contact an Ohlins dealer or other qualified person for advice.

2. Please study and make certain that you fully understand all the mounting instructions and the owners manuals before handling this steering damper kit. If you have any questions regarding proper installation procedures, contact an Ohlins dealer or other qualified person.

3. The vehicle service manual must be referred to when installing the Ohlins steering damper.

Ohlins products are subject to continual improvement and development. Consequently, although these instructions include the most up-to-date information available at the time of printing, there may be minor differences between your suspension and this manual. Please consult your Ohlins dealer if you have any questions with regard to the contents of the manual.

NOTE!

During storage and transportation, especially at high ambient temperature, the oil and grease used for assembling may run out inside the packing and damage the expanded polystyrene packing material. This is not unusual and is in no way detrimental to the steering damper.

Kit contents

Before installing the steering damper, please check the contents of the kit. If anything is missing, contact your Ohlins dealer.

Description	Pcs.	Part No.
Steering damper stroke 63	1	02260-10
Bracket assy	1	02230-01
Frame bracket	1	02272-14
Triple clamp bracket	1	02270-23
Bolt M6SF 8x45	1	00432-05
Bolt M6GS 8x20	1	01046-13
Screw K6S 8x20	2	05404-02
Sleeve	1	02238-04
Teflon spacer	1	02259-01
Sticker Ohlins	2	00192-01
Sticker Ohlins	2	00194-10
Owners manual	1	

Mounting Instructions

- 1** Put the motorcycle on a stand and make sure it's steadily fixed so it will not fall over.
- WARNING!**
- 1.** It's advisable to have an Ohlins dealer or other qualified person to fit your steering damper.
- 2.** Instructions in the vehicle service manual are to be followed when changing the steering damper.
- 3.** When working on a lifted vehicle it must be securely supported to prevent it from falling.
- 2** Loosen the the forward fuel tank attachment.
- 3** Fit the frame bracket. Use the bolt (01046-13) supplied to refit the fuel tank and mount the bracket.
- 4** Fit the triple clamp bracket to the right side of the triple clamp. Use the sleeve and the bolt (00432-05) supplied.
- 5** Fit the bracket assy to the frame bracket. Use the teflon spacer and the bolt (05404-02) supplied.
- 6** Fit the Ohlins steering damper to the bracket assy. Do not tighten yet.
- 7** Fit the end eye of the steering damper to the triple clamp bracket. Use bolt (05404-02) supplied.

